

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 November 2005 (10.11.2005)

PCT

(10) International Publication Number  
**WO 2005/106097 A1**

(51) International Patent Classification<sup>7</sup>: **D06F 33/02**

(21) International Application Number:

PCT/KR2005/001270

(22) International Filing Date: 2 May 2005 (02.05.2005)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:  
10-2004-0030968 3 May 2004 (03.05.2004) KR

(71) Applicant (for all designated States except US): LG  
ELECTRONICS, INC. [KR/KR]; 20 Yoido-dong,  
Youngdungpo-gu, Seoul 150-875 (KR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): LEE, Phal-Jin  
[KR/KR]; 103-405 DaeGwang Apt. YeoJwa-dong, Jin-  
hae-si, Kyungsangnam-do 645-250 (KR).


(74) Agent: HAW, Yong-Noke; 8th Fl. Songchon Bldg.,  
642-15, Yoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: DRUM TYPE WASHING MACHINE AND CONTROLLING METHOD THEREOF



(57) Abstract: A drum type washing machine and controlling method thereof is provided. In the drum type washing machine, a tub is provided, a drum is installed in the tub to rotate about a horizontal axis, a driving motor rotates the drum, a key input unit receives a washing instruction from a user, a memory stores a reference value for an eccentricity of the drum, a microcomputer controls washing and rinsing operations in accordance with a procedure set by the user upon an input of a start command through the key input unit and its prevents repetition of a preliminary spin drying operation using a measured eccentricity of the drum, and a driving control unit controls velocity of the driving motor in accordance with a control signal of the microcomputer.

WO 2005/106097 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*